

- » Brass Sanitary Fittings
- » Brass Cable Glands
- » Cable Gland Accessories
- » Brass Fasteners
- » Copper Lugs Copper Cable terminals
- » Panel Board Accessories
- » Brass Earthing Accessories
- » Brass- Bronze Conductor Clips Clamps
- » Brass Split Bolt Connectors Line Taps
- » Brass Connectors Electronic Connectors
- » Copper Fittings
- » Stainless Steel Parts Components
- » Brass Nuts
- » Brass Screws
- » Sheet Metal Parts Components
- » Copper Brass Pressed Parts Pressed Components
- » Terminal Blocks Brass Terminals
- » Brass Castings Bronze Casting
- » Brass Hose Barbs Hose Nipples
- » Brass Neutral Links
- » Brass - Bronze Pipe Fittings
- » Brass Inserts Plastic Moulding Inserts

■ Cable Glands Brass Cable Glands

A2 Type Brass Cable Gland



| | |
|------------|--|
| Features | To BS 6121 pt. 1 suitable for unarmoured plastic or rubber sheathed cables for indoor as well as outdoor applications. |
| Gland Size | from 16 mm to 75 mm |

Alco Brass Cable Glands



| | |
|----------|--|
| Features | Used with SWA, plastic and rubber sheathed electrical cables. Used indoor conditions.inner ring ensures positive |
|----------|--|

- » Electrical Switchgear Parts
- » Brass Electrical Accessories
- » Brass Electrical Components
- » Brass Fittings
- » Brass Plumbing Fittings
- » Electrical Conduit Fittings
- » Copper Castings
- » Stainless Steel Fittings
- » Stainless Steel Compression Fittings
- » Bronze Fittings
- » Brass Anchors
- » Brass Anchor Fasteners
- » Pipe Brackets - Pipe Support Systems
- » Brass Pipe Clamps Copper Pipe Clamps
- » Brass Stainless Steel Hose Couplings
- » Brass Machine Screws
- » Electrical Conduit Boxes
- » Non Ferrous Casting Foundry
- » Brass Hex Nuts
- » Brass DIN 934 Full Nuts
- » Brass Lock Nuts - Jam nuts
- » Brass Metric Nuts Panel nuts
- » Brass Copper Pipe Clamps

| | |
|-------------------|--|
| | armor clamp and earth continuity. |
| Gland Size | G 204,G 206,G 254, G 256, G 324,G 326, G 405, G 503, G 505,G 636,G 753,G 755 |

BW2 Parts Brass SWA Cable Glands



| | |
|-------------------|---|
| Features | To BS 6121 pt. 1 most suitable for single wire armoured, plastic or rubber (Elastomer) sheathed electrical cables. Used in dry indoor conditions. No loose parts and easy to install. Save times & money. Can be supplied with integral earth facility. |
| Gland size | 20mm to 75mm (S & L) |
| IP Rating | IP 54 |

BW3 Parts Brass SWA Cable Glands



| | |
|--------------------|--|
| Features | TO BS 6212 pt. 1 most suitable for SWA plastic or rubber sheathed cables. Used indoor conditions. Seperate locking ring helps to clamp the armour properly Can be supplied with integral earth facility. |
| Gland Sizes | 20mm to 75mm (S & L) |
| IP rating | IP 54 |

Cable Gland Kit



Gland Kit is a ready to use pack containing glands, Lock Nuts, Earth Tags and PVC Shrouds. Contains two sets upto 32mm and one set for bigger size. It is a convenient way for the user to purchase complete cable termination as he is assured of all the required parts.

Free header cards with customer name and logo can be provided. All BW CW E1W A2 CX CXT glands, kits and gland packs confirm to BS 6121 ensuring smooth termination of electrical cables.

CW Brass Cable Glands



| | |
|-------------------|--|
| Features | To BS 6121 pt. most suitable for SWA armoured plastic or rubber sheathed electric cables Outer seal grips sheath of cable. for use in most climatic conditions Weather proof and water proof design. Has seperate armour lock rings. can be supplied with integral earth facility. |
| Gland Size | 20 mm to 75 mm (S & L) |
| IP rating | IP 66 |

EW1 Brass Cable Glands



| | |
|--------------------|---|
| Features | To BS 6121 pt. 1 suitable for SWA or rubber sheathed cables. Outer seal grips bedding layer of cable. for use in most climatic conditions Weather proof and water proof. Design has seperate armour lock rings. can be supplied with integral earth facility. |
| Gland sizes | 20 mm to 75 mm (S & L) |
| IP rating | IP 66 |

PG Threaded Brass Cable Glands



| | |
|-------------------|---|
| Features | To DIN - 46320 / 46255 available with strain relief facility. With round or hex intermediate sockets and long and short antithreads. Takes all sorts of electrical cables . |
| Gland Size | PG 9 to PG 56 |

TRS Brass Cable Glands



| | |
|-------------------|---|
| Features | While not manufactured to a specific standard, are accepted by many contractors and users as satisfactory method of securing flexible cables. |
| Gland Size | 16m to 32mm |

Cable Glands Brass Cable Glands

Other Terms : **cable glands, waterproof cable gland, brass cable, pg cable glands, brass cable gland India, brass cable gland jamnagar**

Brass Fittings India

Visit Our Site ➡ <http://www.brassfittingsindia.com>

Address : Plot 10/B GIDC Industrial Estate
Jamnagar 361005 **INDIA.**

Contact No : +91 (22) 43449300

Fax No : +91 (22) 22834046

Email Id : sales@brassfittingsindia.com